

# CATTRON™ FOR INDUSTRIAL TOGGLE CONTROLLER



## DURABILITY PLUS LIGHTWEIGHT CONVENIENCE

The toggle controller has a unique shape and style that provides the equipment operator with a controller that is durable, lightweight, ergonomic and convenient. Designed for heavy-duty applications, this controller is ideal for a variety of indoor and outdoor industrial uses. The Toggle Controller employs advanced microcomputer electronics and utilizes surface mount technology. It can be used with Cattron™ AT and MP series receiver/decoder units. It can be used with existing systems as either a replacement or as a spare controller. In addition, the Toggle Controller meets the FCC's requirements regarding narrowband and 12.5 kHz band widths.

## DURABLE CONSTRUCTION

The Toggle Controller has a highly advanced encoder circuit board which is built using industrial grade components, a powerful microcomputer, and sophisticated operating software. All components are protected by a thick-walled, epoxy-coated, extruded aluminum case. The ends of the housing are rubberized metal plates that make shock absorbing end bumpers. This housing carries a lifetime warranty. Only the


highest quality mil-spec toggle switches are used. These switches have gold-plated contacts and a pinned shaft to prevent damage from direct end-on impacts. Their reliability and construction has been field-tested and proven under extreme conditions. Total water and dust sealing makes the entire unit suitable for indoor and outdoor operation.

## POWER SOURCE

The Toggle Controller is powered with disposable alkaline or rechargeable Ni-Cad batteries. In normal operation, a green LED blinks with each function command message. For added safety and improved performance, the operating voltage is regulated over the entire battery life, insuring constant range and reliable operations. When the battery becomes low, the green LED will change to red and a beeping sound will alert the operator that the battery needs to be changed or recharged. Whether you choose disposable or rechargeable batteries, changing the battery is easy - simply open the gasketed battery cover, drop the battery in place and close the cover.

## FEATURES

- Use with most Cattron AT or MP systems
- FCC Narrowband compliant models available
- Customized layout with custom-engraved nameplates
- Rugged design for use in harsh environments
- Rubberized end caps and switch guard
- Push to Operate (PTO) safety bar
- Two-stage LED battery indicator with audible beep
- Power-on self-diagnostics
- Designed for long battery life and ease of service





## TECHNICAL DATA AND SPECIFICATIONS

Case Material	Epoxy- coated aluminum extrusion with molded rubber end caps
Weight	3.0 lbs (1.3 kg) with battery
Dimensions	Approx. 9.8" H x 3.6" W x 4.1" D (25cm x 9.1cm x 10.4 cm)
Environmental	-22° F to +140° F (-30° C to +60° C), Indoor/outdoor use; contact for extremes
Switch Types	Toggle, Push Button, Paddle, Rotary, Lever type switches (stepped or stepless)
Number of Functions	Up to 40 Digital and/or 2 Analog
Keylock Switch	Optional (Power ON/OFF)
Antenna	Internal standard or external optional
Additional Functions	Contact factory or sales representative for details
Aux Functions	Up to 15 digital ON/OFF
Push to Operate (PTO) bar	Standard
Battery Voltage	12.5 VDC nominal
Radio Transmitters	UHF, pulsed packet data, FSK
Approvals	USA, Canada, UK, South Africa, Brazil; Contact for complete listing
Power Output	Variable - dependant upon application requirements and licensing limitations
Emission/Modulation	14KOF1D +/-5 KHz deviation; 9KOF1D +/-2.5 KHz deviation (narrowband)
Operating Range	Greater than 300 ft. (93m) line of sight
Continuous Battery	Alkaline ; Ni-Cad - Battery life dependant upon application
Carrying Case	Optional shoulder strap and/or swivel belt clip, can also be used with ergonomic vest harness

## OPERATION

The standard toggle controller can be configured in a variety of ways and can include pushbuttons or paddles to meet user requirements. All functions are identified by durable custom engraved faceplates. A large safety bar is provided to function as an enabling device to all toggle switches. The large bar is easily and naturally activated by the palm of the operator's hand any time he/she places his/her hand into position to move the toggle switches. The push-to-operate safety bar will electronically disconnect all lever switches when it is released, thus stopping motion commands from these switches. This feature is programmable.

Certain applications may have some toggle switches removed from the control of the PTO bar. Toggle controllers are equipped with a tilt switch to activate diagnostics and can be optionally programmed to send a function. This function can be assigned in the decoder for a variety of operations, i.e., to stop the equipment, sound an alarm or both. Every toggle controller may also be equipped with an optional PC-compatible diagnostic port.

博因（上海）智能化设备有限公司—凯特龙遥控器中国独家代理商

咨询热线：15821100378(微信同号)

QQ：3007276911

邮箱：15821100378@163.com

官网：[www.boyinshanghai.com](http://www.boyinshanghai.com)



Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.